



Technical Requirements:

1. Please use the grease specified by our company (LF-2 or F-3).
2. The * in the drawing is the installation reference size, please follow the installation size requirements.
3. For details of size, please confirm with the delivery specification drawings.

| | | | | | | | | | | | | | | | | | | |
|-------------------------|-------|----------------------------------|---------|-------|-----------------|---------------------------------|------|---|------|--|------|--------------------------------------|-------|---|---|----------|--------|-------------|
| specification drawings. | | | | Model | Reduction ratio | Rated torque at 2000r/min input | | Permissible peak torque at start and stop | | Permissible maximum value for average load | | Permissible maximum momentary torque | | Permissible maximum input rotational speed (Grease) | Permissible average input rotational speed (Grease) | Backlash | weight | Desian life |
| LSD-17-P-XX-U-I | | | | | | Nm | kgfm | Nm | kgfm | Nm | kgfm | Nm | kgfm | r/min | r/min | Arc Sec | Kg | Hour |
| MODEL | U | T | W | | | 17 | 50 | 11 | 1.1 | 23 | 2.3 | 18 | 1.9 | 48 | 4.9 | 7300 | 3500 | ≤20 |
| Wave generator-A φ8 | φ8H7 | 9.4 ^{+0.1} ₀ | 3P9/JS9 | 80 | 14 | 1.4 | 30 | 0.3 | 21 | 2.1 | 58 | 5.9 | 10000 | | | | | |
| Wave generator-A φ15 | φ15H7 | | | 100 | 16 | 1.6 | 37 | 3.8 | 27 | 2.8 | 71 | 7.2 | 10000 | | | | | |